## Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

- 1-17. (Canceled)
- 18. (Currently Amended) Optical recording medium comprising first and second substrates wherebetween there is arranged at least one first photosensitive layer comprising a front face for receiving optical radiation, radiation for writing and/or reading operations by means of the second substrate, substrate; during writing and/or reading operations, medium wherein a first deformable layer, transparent to the optical radiation, radiations and comprising a polymer previously cross-linked by a light radiation, is-arranged between the first photosensitive layer and the second substrate.substrate; wherein the first photosensitive layer comprises an inorganic material able to be locally deformed by the action of a writing optical radiation and the first deformable layer is a layer able to follow the deformations of the photosensitive layer; the first substrate comprises a patterned front face comprising raised parts designed to enable writing and reading of the medium on zones arranged above the raised parts; and the inorganic material is an inorganic material locally deformed in the form of a bubble by the action of a writing optical radiation, wherein the bubble is formed in at least one of the zones arranged above at least one of the raised parts.
  - 19-21. (Canceled)
- 22. (Currently Amended) Medium according to elaim 20, claim 18, wherein the polymer is chosen among silicones.
- 23. (Previously Presented) Medium according to claim 18 wherein the first deformable layer has a thickness less than or equal to 200 micrometers.

- 24. (Currently Amended) Medium according to claim 18, wherein the medium emprises-further comprising a dielectric layer arranged between the first substrate and the first photosensitive layer.
- 25. (Currently Amended) Medium according to claim 18, wherein the medium emprises further comprising a first metal layer arranged between the first substrate and the first photosensitive layer.
- 26. (Currently Amended) Medium according to claim 18, wherein the medium comprises further comprising a layer protecting against oxidation arranged between the first substrate and the first photosensitive layer.
- 27. (Currently Amended) Medium according to claim 18, wherein the medium emprises further comprising a second metal layer arranged between the first photosensitive layer and the first deformable layer.
- 28. (Currently Amended) Medium according to claim 27, wherein further comprising a layer protecting against oxidation, transparent to the optical radiation, is arranged between the second metal layer and the first deformable layer.
- 29. (Currently Amended) Medium according to claim 18, wherein the medium emprises further comprising at least one semi-transparent second photosensitive layer, arranged between the first deformable layer and the second substrate, a second deformable layer being arranged between the second photosensitive layer and the second substrate.
- 30. (Previously Presented) Medium according to claim 29, wherein the second photosensitive layer comprises an inorganic material.
- 31. (Previously Presented) Medium according to claim 29, wherein the second photosensitive layer comprises a patterned front face.
- 32. (Previously Presented) Medium according to claim 29, wherein the first deformable layer comprises a patterned front face.

- 33. (Previously Presented) Medium according to claim 18, wherein the medium is in the form of an optical disc.
- 34. (Previously Presented) Medium according to claim 18, wherein the medium is in the form of a chip card.
- 35. (New) Medium according to claim 18, wherein the inorganic material is a zinc telluride alloy with an atomic proportion of 65% of zinc and 35% of tellurium.
- 36. (New) Medium according to claim 18, wherein a thickness of the deformable layer is greater than a thickness of the photosensitive layer.